

Storage Best Practices

Technical Guide



Storage

- Preferably store inside in a cool, dry area, preferably on racking.
 - If stored outside material must be covered to protect against the elements.
-

Skid Stacking

- It is recommended EasyTrim® skids should only be stacked two high.
 - Whenever possible the lighter skid should always be stacked on top to prevent damage to the bottom skid and possibly damage to the material.
 - EasyTrim® skids can either be picked up at the end using at least 6 ft forklift extensions or they can be picked up from the side.
-

Breaking Bundles

- When breaking apart bundles it is recommended to start by cutting the wrap at the end of the bundle and working your way down the length of the bundle cutting the bag, try not to place the knife directly against the bundle to prevent damage to the trim.
 - It is not recommended to pull the pieces out of the bundle from the end as material may scratch.
-

Loose Piece Packaging

- When wrapping loose trims together they should be arranged in a uniform matter and wrapped tightly with a handheld stretch wrap roller.
 - Material should then be placed in bagging to protect it during transport.
-

Piece Stacking on Skids

- When stacking material onto skids it is recommended to make uniform and level layers on the skid and to prevent creating gaps in the skids as this can cause potential damage when transporting.
 - Lighter material such as the EasyTrim® EZ 01-E should always be placed on top of heavier material such as the EasyTrim® EZ 07-E to prevent any damage to the material.
-

Shipping Skids

- All outbound EasyTrim® material should be transported either on skids or in a suitable sized cardboard box or tube to protect the material.